

Cordless tools
 Li-ion
 Drilling/Fastening
 Impact
 Drilling/Demolition
 Cutting
 Grinding/Sanding
 Sawing
 Planing/Routing
 Outdoor
 Power Equipment
 Dust
 Extractors/Other
 SSP Series
 Pneumatic

Model KP0810K / KP0810CK

850W motor
 CB-132
 • KP0810K

1,050W motor
 CB-132
 • KP0810CK



82mm (3-1/4") Power Planer

Continuous rating Input	850W : KP0810K 1,050W : KP0810CK
Planing width	82mm (3-1/4")
Planing depth	4mm (5/32")
No load speed (rpm)	16,000 : KP0810K 12,000 : KP0810CK
Dimensions (L x W x H)	290 x 168 x 176mm (11-3/8" x 6-5/8" x 6-15/16")
Net weight	3.2kg (7.2lbs) : KP0810K 3.3kg (7.3lbs) : KP0810CK

Model 1100

750W motor
 CB-100A



82mm (3-1/4") Power Planer

Continuous rating Input	750W
Planing width	82mm (3-1/4")
Planing depth	3mm (1/8")
No load speed (rpm)	16,000
Overall length	415mm (16-3/8")
Net weight	4.9kg (10.8lbs)

Model 1600

750W motor
 CB-100A



80mm (3-1/8") Power Planer

Continuous rating Input	750W
Planing width	80mm (3-1/8")
Planing depth	3mm (1/8")
No load speed (rpm)	16,000
Overall length	375mm (14-3/4")
Net weight	5.0kg (11lbs)

Model 1804N

960W motor
 CB-153A



136mm (5-3/8") Power Planer

Continuous rating Input	960W
Planing width	136mm (5-3/8")
Planing depth	3mm (1/8")
No load speed (rpm)	16,000
Overall length	445mm (17-1/2")
Net weight	7.8kg (17.2lbs)

Model 1902

580W motor
 CB-51A



82mm (3-1/4") Power Planer

Continuous rating Input	580W
Planing width	82mm (3-1/4")
Planing depth	1mm (1/32")
No load speed (rpm)	16,000
Overall length	290mm (11-3/8")
Net weight	2.5kg (5.5lbs)

Model 1805N

1,140W motor
 CB-153A



155mm (6-1/8") Power Planer

Continuous rating Input	1,140W
Planing width	155mm (6-1/8")
Planing depth	2mm (1/16")
No load speed (rpm)	15,000
Overall length	445mm (17-1/2")
Net weight	7.9kg (17.4lbs)

Model 2012NB

1,650W motor
 CB-153A



304mm (12") Planer

Continuous rating Input	1,650W
Cutting width	304mm (12")
Cutting depth	Cutting width 0-150mm : 3mm (1/8") Cutting width 150-240mm : 1.5mm (1/16")
Feed rate/min.	8.5m (27.9ft)
Table size (W x L)	304 x 771mm (12" x 30-3/8")
No load speed (rpm)	8,500

Model 2107F

710W motor
 CB-303A



Portable Band Saw

Continuous rating Input	710W
Capacity	Round workpiece (dia.) : 120mm (4-3/4") Rectangular workpiece Without stand : 120mm x 120mm (4-3/4" x 4-3/4")
Blade speed	60m (200ft) - 105m (350ft) / min
Dimensions (L x W x H)	508 x 188 x 256mm (20" x 7-3/8" x 10-1/8")
Net weight	5.7kg (12.6lbs)

Model 2414NB

2,000W motor
 CB-203A



355mm (14") Portable Cut-off

Continuous rating Input	2,000W
Wheel dia.	355mm (14")
Hole dia.	25.4mm (1")
No load speed (rpm)	3,800
Dimensions (L x W x H)	500 x 280 x 600mm (19-11/16" x 11" x 23-5/8")
Net weight	16.2kg (35.7lbs)

Model 2416S

1,430W motor
 CB-153A



405mm (16") Portable Cut-off

Continuous rating Input	1,430W *
Wheel dia.	405mm (16")
Hole dia.	25.4mm (1")
No load speed (rpm)	2,300
Dimensions (L x W x H)	610 x 265 x 535mm (24" x 10-3/8" x 21")
Net weight	20kg (44lbs)

Model LC1230

1,750W motor
 CB-203A



305mm (12") Metal Cutting Saw

Continuous rating Input	1,750W
Capacity	at 90 degrees : 115mm (4-1/2") at 90 degrees : 75 x 150mm (2-15/16" x 5-7/8") at 45 degrees : 90mm (3-1/2") at 45 degrees : 85 x 85mm (3-5/16" x 3-5/16")
No load speed (rpm)	1,300
Dimensions (L x W x H)	516 x 306 x 603mm (20-1/4" x 12" x 23-3/4")

Model 4131

1,100W motor
 CB-303A



185mm (7-1/4") Metal Cutter

Continuous rating Input	1,100W
Blade diameter	185mm (7-1/4")
Capacity	Max. cutting : 63mm (2-1/2")
No load speed (rpm)	3,500
Overall length	358mm (14-1/8")
Net weight	4.8kg (10.6lbs)

Model SG1250

1,400W motor
 CB-318
 AUTO-CUT



125mm (5") Wall Chaser

Continuous rating Input	1,400W
Capacity	Depth : 0-30mm Width : 6-30mm
Blade diameter	125mm (5")
No load speed (rpm)	9,000
Overall length	346mm (13-5/8")
Net weight	4.1kg (9.0lbs)

Model 2702 / 2703

1,650W motor
 CB-153A



210mm (8-1/4") / 255mm (10") Table Saw

Continuous rating Input	1,650W
Capacity	at 90 degrees : 68mm (2-11/16") : 2702 : 91mm (3-9/16") : 2703 at 45 degrees : 47mm (1-3/4") : 2702 : 63mm (2-1/2") : 2703
Blade diameter	210mm (8-1/4") : 2702 255mm (10") : 2703
No load speed (rpm)	4,600

Model MLT100 / MLT100S

1,500W motor



255mm (10") Table Saw

Continuous rating Input	1,500W
Capacity	at 90 degrees : 91mm (3-9/16") at 45 degrees : 63mm (2-1/2")
Blade diameter	255mm (10")
No load speed (rpm)	4,500
Dimensions (L x W x H)	660 x 960 x 330mm (26" x 37-3/4" x 13")
Net weight	38kg (83lbs)

Model 3600H

1,500W motor
 CB-153A



12mm (1/2") Router

Continuous rating Input	1,500W
Capacity	Collet : 12mm or 1/2"
Base dia.	160mm (6-5/16")
No load speed (rpm)	24,000
Overall height	210mm (8-1/4")
Net weight	4.3kg (9.5lbs)

Model 3612

1,650W motor

CB-203A



12mm (1/2") Electronic Router (Plunge type)

Continuous rating Input	1,650W
Capacity	Collet : 12mm or 1/2"
Plunge capacity	0 - 60mm (0 - 2-3/8")
Base dia.	160mm (6-1/4")
No load speed (rpm)	22,000
Overall height	297mm (11-11/16")
Net weight	5.8kg (12.8lbs)



Model 3612BR

1,600W motor

CB-153A



12mm (1/2") Router (Plunge type)

Continuous rating Input	1,600W
Capacity	Collet : 12mm or 1/2"
Plunge capacity	0 - 65mm (0 - 2-9/16")
Base dia.	160mm (6-1/4")
No load speed (rpm)	23,000
Overall height	297mm (11-11/16")
Net weight	5.7kg (12.5lbs)



Model 3612C

1,850W motor

CB-203A



12mm (1/2") Electronic Router (Plunge type)

Continuous rating Input	1,850W
Capacity	Collet : 12mm or 1/2"
Plunge capacity	0 - 60mm (0 - 2-3/8")
Base dia.	160mm (6-1/4")
No load speed (rpm)	9,000-23,000
Overall height	297mm (11-11/16")
Net weight	6.0kg (13.2lbs)



Model RP1800 / RP1800F

1,850W motor



12mm (1/2") Plunge Router

Continuous rating Input	1,850W
Capacity	Collet : 12mm (1/2")
Plunge Capacity	70mm (2-3/4")
No load speed (rpm)	22,000
Net Weight	5.8kg (12.8lbs)

Model RP1801 / RP1801F

1,650W motor



12mm (1/2") Plunge Router

Continuous rating Input	1,650W
Capacity	Collet : 12mm (1/2")
Plunge Capacity	70mm (2-3/4")
No load speed (rpm)	22,000
Net Weight	5.8kg (12.8lbs)

Model RP2300FC / RP2301FC

2,300W motor

RP2300FC

2,100W motor

RP2301FC



12mm (1/2") Plunge Router

Continuous rating Input	2,300W : RP2300FC 2,100W : RP2301FC
Capacity	Collet : 12mm (1/2")
Plunge Capacity	70mm (2-3/4")
No load speed (rpm)	9,000-22,000
Net Weight	6.0kg (13.2lbs)

Model 3709

530W motor

CB-411A



6mm (1/4") Trimmer

Continuous rating Input	530W
Capacity	Collet : 6mm or 1/4"
No load speed (rpm)	30,000
Dimensions (L x W x H)	82 x 90 x 199mm (3-1/4" x 3-1/2" x 7-7/8")
Net weight	1.5kg (3.3lbs)

Model N3701

440W motor

CB-51A



6mm (1/4") Trimmer

Continuous rating Input	440W
Capacity	Collet : 6mm or 1/4"
Base	82 x 90mm (3-1/4" x 3-1/2")
No load speed (rpm)	30,000
Overall height	181mm (7-1/8")
Net weight	1.7kg (3.7lbs)

Model 407

1,050W motor

CB-165



Vacuum Cleaner (Wet&Dry)

Continuous rating Input	1,050W
Max. peak air flow	3.0m³/min
Max. sealed suction (water column)	20.6kpa (2,100mmH ₂ O)
Recoverable capacity	Dust : 32L (8.4gal) Water : 30L (7.8gal)
Overall height	699mm (27-1/2")
Net weight	10.3kg (22.7lbs)



Model 4076DW

7.2V



Cordless Cleaner

Capacity	500mL
Max. air flow	0.9m³/min
Continuous use (minutes)	Hi : 10, Lo : 20
Max. sealed suction (water column)	2.7kpa (270mmH ₂ O)
Overall length	446mm (17-1/2")
Net weight	1.4kg (3.1lbs)
Voltage	7.2V



Model 4014N / 4014NV

600W motor

CB-100A



Blower

Continuous rating Input	600W
Air pressure (water column)	0-560mm (22")
Air volume	28m³/min. (98cu.ft./min.)
No load speed (rpm)	16,000 : 4014N 0-16,000 : 4014NV
Overall length	430mm (16-15/16")
Net weight	1.75kg (3.8lbs)



Model UB1100 / UB1101

600W motor

CB-303A



Blower

Continuous rating Input	600W
Air volume	2.8m³/min : UB1100 0-2.8m³/min : UB1101
Air pressure	5.5kpa (560mm H ₂ O) : UB1100 0-5.5kpa (0-560mm H ₂ O) : UB1101
No load speed (rpm)	16,000 : UB1100 0-16,000 : UB1101
Overall length	480mm (18-7/8")
Net weight	1.7kg (3.7lbs)



Model 4100NB / 4100NH

860W motor

CB-251A

1,300W motor

CB-303A



110mm (4-3/8") Cutter

Continuous rating Input	860W : 4100NB 1,300W : 4100NH
Capacity Max. cutting	34mm (1-5/16")
Blade diameter	110mm (4-3/8")
No load speed (rpm)	11,000 : 4100NB 13,000 : 4100NH
Overall length	218mm (8-5/8") : 4100NB 234mm (9-1/4") : 4100NH
Net weight	2.7kg (5.9lbs) : 4100NB 2.9kg (6.4lbs) : 4100NH



Model 4140

1,050W motor

CB-303A



110mm (4-3/8") Cutter

Continuous rating Input	1,050W
Capacity	at 90 degrees : 34mm (1-3/8") at 45 degrees : 21mm (13/16")
Blade diameter	110mm (4-3/8")
No load speed (rpm)	11,000
Overall length	222mm (8-3/4")
Net weight	2.7kg (6.0lbs)



Model 4191DWA

12V



80mm (3-1/8") Cordless Cutter

Capacity	at 90 degrees : 21.5mm (13/16") at 45 degrees : 16mm (5/8")
Wheel diameter	80mm (3-1/8")
No load speed (rpm)	1,000
Overall length	316mm (12-1/2")
Net weight	2.1kg (4.6lbs)
Voltage	12V

Model 4107R

1,400W motor

CB-153A



180mm (7-1/8") Cutter

Continuous rating Input	1,400W
Capacity	Max. cutting : 60mm (2-3/8")
Blade diameter	180mm (7-1/8")
No load speed (rpm)	5,000
Overall length	370mm (14-9/16")
Net weight	7.2kg (15.8lbs)



Cordless tools
 Li-Ion
 Drilling/Fastening
 Impact
 Drilling/DEMOLITION
 Cutting
 Grinding/Sanding
 Sawing
 Planing/Routering
 Outdoor Power Equipment
 Dust Extraction/Other
 SSP Series
 Pneumatic

Model 4300BA / 4300BV

390W motor
CB-51A



Jig Saw

Continuous rating Input 390W
Capacity In wood at 90 degrees : 55mm (2-1/8")
In steel at 90 degrees : 6mm (1/4")
Length of stroke 26mm (1")
Strokes per minute (spm) 3,100:4300BA / 0-3100:4300BV
Overall length 255mm (10-1/8") : 4300BA
225mm (8-7/8") : 4300BV
Net weight 2.5kg (5.5lbs)

Model 4327 / 4329

450W motor
CB-64A



Jig Saw

Continuous rating Input 450W
Capacity In wood at 90 degrees : 65mm (2-9/16")
In steel at 90 degrees : 6mm (1/4")
Length of stroke 18mm (11/16")
Strokes per minute (spm) 500 - 3,100
Dimensions 224 x 77 x 197mm (L x W x H) (8-7/8" x 3" x 7-3/4")
Net weight 1.9kg (4.2lbs)

Model 4350T / 4350CT

580W motor
CB-419A
• 4350T

720W motor
CB-419A
• 4350CT



Jig Saw

Continuous rating Input 580W : 4350T / 720W : 4350CT
Capacity In wood at 90 degrees : 135mm (5-5/16")
In steel at 90 degrees : 10mm (3/8")
Length of stroke 26mm (1")
Strokes per minute (spm) 2,800 : 4350T / 800 - 2,800 : 4350CT
Dimensions 236 x 73 x 207mm (L x W x H) (9-1/4" x 2-7/8" x 8-1/8")
Net weight 2.5kg (5.5lbs)

Model 5007NF

1,800W motor
CB-153A



185mm (7-1/4") Circular Saw

Continuous rating Input 1,800W
Capacity In wood at 90 degrees : 63.5mm (2-1/2")
at 45 degrees : 45mm (1-3/4")
at 50 degrees : 35mm (1-3/8")
Blade diameter 185mm (7-1/4")
No load speed (rpm) 5,800
Dimensions 317 x 240 x 265mm (L x W x H) (12-1/2" x 9-1/2" x 10-3/8")
Net weight 5.0kg (11lbs)

Model 5008MG

1,800W motor
CB-153A



210mm (8-1/4") Circular Saw

Continuous rating Input 1,800W
Capacity at 90 degrees : 75.5mm (3")
at 45 degrees : 57mm (2-1/4")
Blade diameter 210mm (8-1/4")
No load speed (rpm) 5,200
Overall length 332mm (13-1/8")
Net weight 4.8kg (10.6lbs)

Model 5600NB / 5800NB

800W motor
CB-100A
• 5600NB

900W motor
CB-100A
• 5800NB



160mm (6-1/4") / 180mm (7-1/8") Circular Saw

Continuous rating Input 800W : 5600NB / 900W : 5800NB
Capacity at 90 degrees : 55mm (2-1/8") : 5600NB
: 64mm (2-1/2") : 5800NB
at 45 degrees : 36mm (1-3/8") : 5600NB
: 43mm (1-11/16") : 5800NB
Blade diameter 160mm (6-1/4") : 5600NB
180mm (7-1/8") : 5800NB
No load speed (rpm) 4,000 : 5600NB / 4,500 : 5800NB
Overall length 250mm (9-7/8") : 5600NB / 272mm (10-3/4") : 5800NB
Net weight 3.0kg (6.6lbs) : 5600NB / 3.6kg (7.9lbs) : 5800NB

Model 5606B / 5806B-C

950W motor
CB-303A
• 5606B

1,050W motor
CB-303A
• 5806B-C



160mm (6-1/4") / 185mm (7-1/4") Circular Saw

Continuous rating Input 950W : 5606B / 1,050W : 5806B-C
Capacity at 90 degrees : 55mm (2-1/8") : 5606B
: 66mm (2-5/8") : 5806B-C
at 45 degrees : 36mm (1-3/8") : 5606B
: 44mm (1-11/16") : 5806B-C
Blade diameter 160mm (6-1/4") : 5606B
185mm (7-1/4") : 5806B-C
No load speed (rpm) 4,700
Overall length 268mm (10-9/16") : 5606B / 282mm (11-1/8") : 5806B-C
Net weight 3.1kg (6.8lbs) : 5606B / 3.5kg (7.7lbs) : 5806B-C

Model N5900B

2,000W motor
CB-153A



235mm (9-1/4") Circular Saw

Continuous rating Input 2,000W
Capacity at 90 degrees : 85mm (3-3/8")
at 45 degrees : 60mm (2-3/8")
at 50 degrees : 53mm (2-1/16")
Blade diameter 235mm (9-1/4")
No load speed (rpm) 4,100
Overall length 380mm (15")
Net weight 7.0kg (15.4lbs)

Model 5201N

1,430W motor
CB-153A



260mm (10-1/4") Circular Saw

Continuous rating Input 1,430W
Capacity at 90 degrees : 97mm (3-3/4")
at 45 degrees : 64mm (2-1/2")
Blade diameter 260mm (10-1/4")
No load speed (rpm) 3,700
Overall length 445mm (17-1/2")
Net weight 8.3kg (18.3lbs)

Model 5103N

1,750W motor
CB-153A



335mm (13-1/8") Circular Saw

Continuous rating Input 1,750W
Capacity at 90 degrees : 128mm (5")
at 45 degrees : 91mm (3-5/8")
Blade diameter 335mm (13-1/8")
No load speed (rpm) 2,900
Overall length 505mm (19-7/8")
Net weight 10kg (22lbs)

Model 5402

1,750W motor
CB-153A



415mm (16-5/16") Circular Saw

Continuous rating Input 1,750W
Capacity at 90 degrees : 157mm (6-3/16")
at 45 degrees : 106mm (4-3/16")
Blade diameter 415mm (16-5/16")
No load speed (rpm) 2,200
Overall length 615mm (24-1/4")
Net weight 14kg (30.8lbs)

Model LS1040

1,650W motor
CB-153A



255mm (10") Compound Miter Saw

Continuous rating Input 1,650W
Capacity at 90 degrees : 90.5 x 95mm (3-9/16" x 3-3/4")
at 45 degrees : 90.5 x 67mm (3-9/16" x 2-5/8")
Blade diameter 255 - 260mm (10" - 10-1/4")
No load speed (rpm) 4,600
Dimensions 530 x 532 x 476mm (L x W x H) (20-7/8" x 21" x 18-3/8")
Net weight 11.6kg (25.5lbs)

Model LS1440

1,380W motor
CB-153A



355mm (14") Miter Saw

Continuous rating Input 1,380W
Capacity at 90 degrees : 122 x 152mm (4-13/16" x 6")
at 45 degrees : 115 x 122mm (4-1/2" x 4-13/16")
Blade diameter 355mm (14")
No load speed (rpm) 3,200
Dimensions 596 x 530 x 435mm (L x W x H) (23-1/2" x 20-7/8" x 17-1/8")
Net weight 34kg (75lbs)

Model LS1212

1,650W motor
CB-153A



305mm (12") Slide Compound Saw

Continuous rating Input 1,650W
Capacity at 90 degrees : 98 x 310mm (3-7/8" x 12-1/4")
at 45 degrees : 98 x 220mm (3-7/8" x 8-5/8")
Blade diameter 305mm (12")
No load speed (rpm) 3,200
Dimensions 800 x 590 x 690mm (L x W x H) (31-1/2" x 23-1/4" x 27-1/4")
Net weight 22kg (48.5lbs)

Model BO4510 / BO4540

180W motor
CB-64A
• BO4510

160W motor
CB-64A
• BO4540



Finishing Sander

Continuous rating Input 180W : BO4510 / 160W : BO4540
Pad size 110 x 100mm (4-3/8" x 4")
Abrasive paper size 114 x 140mm (4-1/2" x 5-1/2")
Orbits per minute (opm) 12,000 : BO4510 / 14,000 : BO4540
Overall length 115mm (4-1/2")
Net weight 1.1kg (2.4lbs) : BO4510
0.9kg (1.98lbs) : BO4540

Model BO4555 / BO4556 / BO4557

200W motor
CB-419A
• BO4555/BO4556

180W motor
CB-419A
• BO4557



Finishing Sander

Continuous rating Input 200W / 180W : BO4557
Pad size 112 x 102mm (4-3/8" x 4")
Abrasive paper size 114 x 140mm (4-1/2" x 5-1/2")
Dimensions 131 x 112 x 141mm (5-1/8" x 4-3/8" x 5-9/16")
(L x W x H)
131 x 112 x 137mm (5-1/8" x 4-3/8" x 5-3/8") : BO4557
Orbits per minute (opm) 14,000
Net weight 1.1kg (2.4lbs) : BO4555 / BO4556
0.9kg (2.0lbs) : BO4557

Model B04565

200W motor

CB-419A



Finishing Sander

Continuous rating Input	200W
Pad size	112 x 190mm (4-3/8" x 7-1/2")
Abrasive paper size	114 x 102mm (4-1/2" x 4")
Triangle	96mm (3-3/4")
Orbits per minute (opm)	14,000
Dimensions (L x W x H)	219 x 112 x 139mm (8-5/8" x 4-3/8" x 5-1/2")
Net weight	1.1kg (2.4lbs)



Model B03700

180W motor

CB-64A



Finishing Sander

Continuous rating Input	180W
Pad size	93 x 185mm (3-5/8" x 7-1/4")
Abrasive paper size	93 x 228mm (3-5/8" x 9")
Orbits per minute (opm)	10,000
Overall length	254mm (10")
Net weight	1.4kg (3.1lbs)



Model B04901

330W motor

CB-419A



Finishing Sander

Continuous rating Input	330W
Pad size	115 x 229mm (4-1/2" x 9")
Abrasive paper size	115 x 280mm (4-1/2" x 11")
Orbits per minute (opm)	10,000
Overall length	289mm (11-3/8")
Net weight	2.8kg (6.2lbs)



Model 9045B

520W motor

CB-100A



Finishing Sander

Continuous rating Input	520W
Pad size	114 x 234mm (4-1/2" x 9-1/4")
Abrasive paper size	114 x 280mm (4-1/2" x 11")
Orbits per minute (opm)	10,000
Overall length	240mm (9-1/2")
Net weight	2.6kg (5.7lbs)



Model 9045N

520W motor

CB-100A



Finishing Sander

Continuous rating Input	520W
Pad size	114 x 234mm (4-1/2" x 9-1/4")
Abrasive paper size	114 x 280mm (4-1/2" x 11")
Orbits per minute (opm)	10,000
Overall length	268mm (10-5/8")
Net weight	2.8kg (6.2lbs)



Model 9910

650W motor

CB-411A



76mm x 457mm (3" x 18") Belt Sander

Continuous rating Input	650W
Belt size	76 x 457mm (3" x 18")
Belt speed	270m/min. (900ft/min)
Overall length	262mm (10-5/16")
Net weight	2.6kg (5.7lbs)
Power supply cord	2.5m (8.2ft)



Model 9031

550W motor

CB-411A



30mm x 533mm (1-3/16" x 21") Belt Sander

Continuous rating Input	550W
Belt size	30 x 533mm (1-3/16" x 21")
Belt speed	200-1,000m/min. (656-3,280ft/min)
Overall length	380mm (15")
Net weight	2.1kg (4.6lbs)



Model 9401

940W motor

CB-153A



100mm x 610mm (4" x 24") Belt Sander

Continuous rating Input	940W
Belt size	100 x 610mm (4" x 24")
Belt speed	350m/min. (1,150ft/min)
Overall length	374mm (14-3/4")
Net weight	7.3kg (16.1lbs)



Model 9402

1,040W motor

CB-153A



100mm x 610mm (4" x 24") Belt Sander

Continuous rating Input	1,040W
Belt size	100 x 610mm (4" x 24")
Belt speed	Hi : 350m (1,150ft/min) Lo : 300m (984ft/min)
Overall length	374mm (14-3/4")
Net weight	7.3kg (16.1 lbs)



Model 9403

1,200W motor

CB-303A



100mm x 610mm (4" x 24") Belt Sander

Continuous rating Input	1,200W
Belt size	100 x 610mm (4" x 24")
Belt speed	500m/min. (1,640ft/min)
Overall length	353mm (13-7/8")
Net weight	5.9kg (13lbs)



Model 9924DB

850W motor

CB-100A



76mm x 610mm (3" x 24") Belt Sander

Continuous rating Input	850W
Belt size	76 x 610, 620mm (3" x 24, 24-3/8")
Belt speed	400m/min. (1,300ft/min)
Overall length	355mm (14")
Net weight	4.8kg (10.6lbs)



Model 903

105W motor

CB-1



3mm (1/8") Mini Grinder

Continuous rating Input	105W
Capacity	Collet : 3mm or 1/8"
No load speed (rpm)	30,000
Overall length	195.5mm (7-3/4")
Net weight	0.6kg (1.3lbs)



Model 906

240W motor

CB-64A



6mm (1/4") Die Grinder

Continuous rating Input	240W
Capacity	Collet : 6mm or 1/4"
No load speed (rpm)	25,000
Overall length	283mm (11-1/8")
Net weight	0.9kg (2lbs)



Model 906H

320W motor

CB-65A



6mm (1/4") Die Grinder

Continuous rating Input	320W
Capacity	Collet : 6mm or 1/4"
No load speed (rpm)	27,000
Overall length	355mm (14")
Net weight	1.9kg (4.2lbs)

Model GD0600 / GD0601

400W motor

CB-325



6mm (1/4") Die Grinder

Continuous rating Input	400W
Capacity	Collet : 6mm or 1/4"
Wheel dia.	38mm (1-1/2")
No load speed (rpm)	25,000
Dimensions (L x W x H)	358 x 82 x 82mm (14-1/8" x 3-1/4" x 3-1/4")
Net weight	1.6kg (3.5lbs)



Model GD0800 / GD0800C

500W motor

CB-325

GD0800

750W motor

CB-318

AUTO-CUT

GD0800C



8mm (1/4") Die Grinder

Continuous rating Input	500W : GD0800 750W : GD0800C
Capacity	Collet : 8mm (1/4") : GD0800 Collet : 8.6mm (1/4") : GD0800C
No load speed (rpm)	28,000 : GD0800 7,000-28,000 : GD0800C
Overall length	371 x 75 x 75mm : GD0800 371mm (14-5/8") : GD0800C
Net weight	1.6kg (3.5lbs)



Cordless tools
 Li-Ion
 Drilling/Fastening
 Impact
 Drilling/DEMOLITION
 Cutting
 Grinding/Sanding
 Sawing
 Planning/Routing
 Outdoor
 Power Equipment
 Dust
 Extraction/Other
 SSP Series
 Pneumatic

Model GD0810C

750W motor
CB-318
AUTO-CUT



8mm (1/4") Die Grinder

Continuous rating Input	750W
Capacity	Collet: 8, 6mm or 1/4"
No load speed (rpm)	1,800-7,000
Overall length	371mm (14-5/8")
Net weight	1.7kg (3.7lbs)

Model 9105

750W motor
CB-153A



125mm (5") Straight Grinder

Continuous rating Input	750W
Max. wheel size	125 x 19mm (5" x 3/4")
Hole dia.	12.7mm (1/2")
No load speed (rpm)	4,800
Overall length	550mm (21-5/8")
Net weight	5.5kg (12lbs)

Model GB602 / GB602W

250W motor



Bench Grinder

Continuous rating Input	250W
Max. wheel size	150 x 16mm (6" x 5/8")
	: GB602
	150 x 16, 6.4mm (5" x 5/8, 1/4")
	: GB602W
Hole dia.	12.7mm (1/2")
H.P.	1/3
No load speed (rpm)	2,850 (50Hz) / 3,450 (60Hz)
Net weight	9.4kg (20.7lbs) : GB602
	9.5kg (20.9lbs) : GB602W

Model GB801

550W motor



205mm (8") Bench Grinder

Continuous rating Input	550W
Max. wheel size	205 x 19mm (8" x 3/4")
Hole dia.	15.88mm (5/8")
H.P.	3/4
No load speed (rpm)	2,850 (50Hz) / 3,450 (60Hz)
Dimensions	395 x 265 x 333mm
(L x W x H)	(15-9/16" x 10-7/16" x 13-7/64")
Net weight	20.5kg (45.1lbs)

Model GV6010

440W motor
CB-64A



150mm (6") Disc Sander

Continuous rating Input	440W
Capacity	Abrasive disc : 150mm (6")
	Pad : 120mm (4-3/4")
No load speed (rpm)	4,500
Dimensions	200 x 74 x 181mm
(L x W x H)	(7-7/8" x 2-15/16" x 7-1/8")
Net weight	1.1kg (2.4lbs)

Model 9218SB

570W motor
CB-100A



180mm (7") Disc Sander

Continuous rating Input	570W
Capacity	Wire cup brush : 110mm (4-3/8")
	Abrasive disc : 180mm (7")
No load speed (rpm)	4,500
Overall length	225mm (8-7/8")
Net weight	2.7kg (6.0lbs)

Model 9218PB / 9218PBL

570W motor
CB-100A



180mm (7") Polisher

Continuous rating Input	570W
Capacity	Wool bonnet : 180mm (7")
No load speed (rpm)	2,000 : 9218PB
	1,400 : 9218PBL
Overall length	235mm (9-1/4")
Net weight	2.9kg (6.4lbs)

Model 9207SPB

700W motor
CB-100A



180mm (7") Sander Polisher

Continuous rating Input	700W
Capacity	Abrasive disc : 180mm (7")
	Diamond wheel : 180mm (7")
No load speed (rpm)	2,000 / 3,800
Overall length	455mm (17-7/8")
Net weight	3.4kg (7.5lbs)

Model 9227C

1,200W motor
CB-303A



180mm (7") Sander Polisher

Continuous rating Input	1,200W
Capacity	Abrasive disc : 180mm (7")
	Wool pad : 180mm (7")
No load speed (rpm)	0 - 3,000
Overall length	470mm (18-1/2")
Net weight	3.0kg (6.6lbs)

Model 6904VH

360W motor
CB-415A



12.7mm (1/2") Impact Wrench

Continuous rating Input	360W *
Capacity	Standard bolt : M10 - M16 (3/8" - 5/8")
	High tensile bolt : M10 - M12 (3/8" - 1/2")
	Square drive : 12.7mm (1/2")
Impacts per minute (ipm)	Hi : 0-3,000 / Lo : 0-2,500
No load speed (rpm)	Hi : 0-2,400 / Lo : 0-2,100
Max. fastening torque	Hi : 196N.m (145ft.lbs)
	Lo : 147N.m (109ft.lbs)
Overall length	265mm (10-3/8")

Model 6905B

440W motor
CB-65A



12.7mm (1/2") Impact Wrench

Continuous rating Input	440W
Capacity	Standard bolt : M12 - M20 (1/2" - 3/4")
	High tensile bolt : M12 - M16 (1/2" - 5/8")
	Square drive : 12.7mm (1/2")
Impacts per minute (ipm)	2,000
No load speed (rpm)	1,700
Max. fastening torque	294N.m (220ft.lbs)
Overall length	270mm (10-5/8")

Model 6905H

470W motor
CB-415A



12.7mm (1/2") Impact Wrench

Continuous rating Input	470W
Capacity	Standard bolt : M12 - M20 (1/2" - 3/4")
	High tensile bolt : M12 - M16 (1/2" - 5/8")
	Square drive : 12.7mm (1/2")
Impacts per minute (ipm)	2,600
No load speed (rpm)	2,200
Max. fastening torque	294N.m (220ft.lbs)
Overall length	275mm (10-7/8")

Model 6906

850W motor
CB-100A



19mm (3/4") Impact Wrench

Continuous rating Input	850W
Capacity	Standard bolt : M16 - M22 (5/8" - 7/8")
	High tensile bolt : M16 - M20 (5/8" - 3/4")
	Square drive : 19mm (3/4")
Impacts per minute (ipm)	1,600
No load speed (rpm)	1,700
Max. fastening torque	588N.m (441ft.lbs)
Overall length	327mm (12-7/8")

Model TW0200 / TW0350

380W motor + TW0200
400W motor + TW0350
CB-411A



12.7mm (1/2") Impact Wrench

Continuous rating Input	380W / 400W
Capacity	Standard bolt : M10 - M16 (3/8" - 5/8") : TW0200
	High tensile bolt : M10 - M12 (3/8" - 1/2") : TW0200
	Square drive : 12.7mm (1/2") : TW0200
	Standard bolt : M12 - M22 (1/2" - 7/8") : TW0350
	High tensile bolt : M12 - M16 (1/2" - 5/8") : TW0350
	Square drive : 12.7mm (1/2") : TW0350
Impacts per minute (ipm)	0-2,200 : TW0200 / 2,000 : TW0350
No load speed (rpm)	0-2,200 : TW0200 / 2,000 : TW0350
Max. fastening torque	200N.m (150ft.lbs) / 350N.m (260ft.lbs)

Model TW1000

1,200W motor
CB-153A



25.4mm (1") Impact Wrench

Continuous rating Input	1,200W
Capacity	Standard bolt : M24 - M30 (1 5/16" - 1 3/16")
	High tensile bolt : M22 - M24 (7/8" - 15/16")
	Square drive : 25.4mm (1")
Impacts per minute (ipm)	1,500
No load speed (rpm)	1,400
Max. fastening torque	1,000N.m (738ft.lbs)
Overall length	382mm (15")
Net weight	8.4kg (18.5lbs)

Model 9500NB

570W motor
CB-411A



100mm (4") Angle Grinder

Continuous rating Input	570W
Capacity	Depressed center wheel : 100mm (4")
	Wire cup brush : 75mm (3")
	Abrasive disc : 100mm (4")
	Diamond wheel : 110mm (4-3/8")
No load speed (rpm)	12,000
Overall length	253mm (10")
Net weight	1.5kg (3.3lbs)

Model 9553B / 9553BX

710W motor
 CB-325



100mm (4") Angle Grinder

Continuous rating Input	710W
Capacity	Depressed center wheel : 100mm (4")
	Wire cup brush : 75mm (3")
	Abrasive disc : 100mm (4")
	Diamond wheel : 100mm (4")
No load speed (rpm)	11,000
Dimensions (L x W x H)	258 x 118 x 97mm
Net weight	1.4kg (3.1lbs)

Model 9556NB / 9556HN

840W motor
 CB-325



100mm (4") Angle Grinder

Continuous rating Input	840W
Capacity	Depressed center wheel : 100mm (4")
	Abrasive disc : 100mm (4")
	Diamond wheel : 100mm (4")
No load speed (rpm)	11,000
Dimensions (L x W x H)	271 x 118 x 97mm
Net weight	1.6kg (3.5lbs)

Model 9556HP

840W motor
 CB-325



100mm (4") Angle Grinder

Continuous rating Input	840W
Capacity	Depressed center wheel : 100mm (4")
	Abrasive disc : 100mm (4")
	Diamond wheel : 100mm (4")
No load speed (rpm)	11,000
Dimensions (L x W x H)	273 x 118 x 97mm
Net weight	1.6kg (3.5lbs)

Model 9533B / 9533BL

720W motor
 CB-411A



100mm (4") Angle Grinder

Continuous rating Input	720W
Capacity	Depressed center wheel : 100mm (4")
	Wire cup brush : 75mm (3")
	Abrasive disc : 100mm (4")
	Diamond wheel : 110mm (4-3/8")
No load speed (rpm)	12,000 : 9533B / 9,000 : 9533BL
Dimensions (L x W x H)	262 x 118 x 104mm
Net weight	1.4kg (3.1lbs)

Model 9533 / 9533L

720W motor
 CB-411A



100mm (4") Angle Grinder

Continuous rating Input	720W
Capacity	Depressed center wheel : 100mm (4")
	Wire cup brush : 75mm (3")
	Abrasive disc : 100mm (4")
	Diamond wheel : 110mm (4-3/8")
No load speed (rpm)	12,000 : 9533 / 9,000 : 9533L
Dimensions (L x W x H)	262 x 118 x 104mm
Net weight	1.4kg (3.1lbs)

Model 9005N / 9006N

1,020W motor
 CB-100A



125mm (5") / 150mm (6") Angle Grinder

Continuous rating Input	1,020W
Capacity	Depressed center wheel : 125mm (5") / 150mm (6")
	Abrasive disc : 125mm (5") / 150mm (6")
	Diamond wheel : 125mm (5") / 150mm (6")
No load speed (rpm)	11,000
Overall length	356mm (14")
Spindle thread	M16 x 2
Net weight	2.5kg (5.5lbs)

Model GA4030

720W motor
 CB-459/460



100mm (4") Angle Grinder

Continuous rating Input	720W
Capacity	100mm (4")
No load speed (rpm)	11,000
Overall length	180mm (7-1/8")
Dimensions (L x W x H)	266 x 118 x 104mm
Net weight	1.4kg (3.1lbs)

Model 9015B / 9016B

1,050W motor
 CB-303A



125mm (5") / 150mm (6") Angle Grinder

Continuous rating Input	1,050W
Capacity	Depressed center wheel : 125mm (5") / 150mm (6")
	Wire cup brush : 90mm (3-1/2")
	Abrasive disc : 125mm (5") / 150mm (6")
	Diamond wheel : 125mm (5") : 9015B
	Cut-off wheel : 150mm (6") : 9016B
No load speed (rpm)	10,000 : 9015B / 9,000 : 9016B
Overall length	381mm (15")
Net weight	2.4kg (5.3lbs)

Model GA5010 / GA5020

1,050W motor
 CB-303A



125mm (5") Angle Grinder

Continuous rating Input	1,050W
Capacity	Depressed center wheel : 125mm (5")
	Abrasive disc : 125mm (5")
	Diamond wheel : 125mm (5")
No load speed (rpm)	11,000
Dimensions (L x W x H)	GA5010 : 356 x 139 x 112mm (14" x 5-1/2" x 4-3/8")
	GA5020 : 356 x 139 x 120mm (14" x 5-1/2" x 4-3/4")
Net weight	2.2kg (4.8lbs)

Model GA6010 / GA6020

1,050W motor
 CB-303A



150mm (6") Angle Grinder

Continuous rating Input	1,050W
Capacity	Depressed center wheel : 150mm (6")
	Abrasive disc : 150mm (6")
	Diamond wheel : 150mm (6")
No load speed (rpm)	10,000
Dimensions (L x W x H)	GA6010 : 356 x 169 x 112mm (14" x 6-5/8" x 4-3/8")
	GA6020 : 356 x 169 x 120mm (14" x 6-5/8" x 4-3/4")
Net weight	2.2kg (4.8lbs)

Model 9077

2,000W motor
 CB-204A
 AUTO-CUT



180mm (7") Angle Grinder

Continuous rating Input	2,000W
Capacity	Depressed center wheel : 180mm (7")
	Wire cup brush : 110mm (4-3/8")
No load speed (rpm)	7,600
Overall length	484mm (19-1/16")
Net weight	5.3kg (11.6lbs)

Model 9617

2,000W motor
 CB-204A
 AUTO-CUT



180mm (7") Angle Grinder

Continuous rating Input	2,000W
Capacity	Depressed center wheel : 180mm (7")
	Wire cup brush : 110mm (4-3/8")
No load speed (rpm)	8,500
Overall length	458mm (18")
Net weight	4.9kg (10.8lbs)

Model 9607NB

1,800W motor
 CB-153A



180mm (7") Disc Grinder

Continuous rating Input	1,800W
Capacity	Depressed center wheel : 180mm (7")
	Wire cup brush : 110mm (4-3/8")
	Abrasive disc : 180mm (7")
	Diamond wheel : 180mm (7")
No load speed (rpm)	8,000
Overall length	413mm (16-1/4")
Net weight	5kg (11lbs)

Model GA7001

2,000W motor
 CB-153A



180mm (7") Disc Grinder

Continuous rating Input	2,000W
Capacity	Depressed center wheel : 180mm (7")
	Wire cup brush : 110mm (4-3/8")
	Abrasive disc : 180mm (7")
	Diamond wheel : 180mm (7")
No load speed (rpm)	8,000
Overall length	411.5mm (16-1/4")
Net weight	5.7kg (12.6lbs)

Model GA7020 / GA9020

2,200W motor
 CB-204A
 AUTO-CUT



180mm (7") / 230mm (9") Angle Grinder

Continuous rating Input	2,200W
Capacity	Depressed center wheel : 180mm (7") / 230mm (9")
	Wire cup brush : 110mm (4-3/8")
	Cut-off wheel : 180mm (7") / 230mm (9")
No load speed (rpm)	8,500 : GA7020 / 6,600 : GA9020
Dimensions (L x W x H)	GA7020 : 473 x 200 x 140mm (18-5/8" x 7-7/8" x 5-1/2")
	GA9020 : 473 x 249 x 140mm (18-5/8" x 9-3/4" x 5-1/2")
Net weight	4.7kg (10.4lbs)

Model GA7030 / GA9030

2,400W motor
 CB-204A
 AUTO-CUT



180mm (7") / 230mm (9") Angle Grinder

Continuous rating Input	2,400W
Capacity	Depressed center wheel : 180mm (7") / 230mm (9")
	Wire cup brush : 110mm (4-3/8")
	Cut-off wheel : 180mm (7") / 230mm (9")
Hole dia.	22, 23mm (7/8")
No load speed (rpm)	8,500 : GA7030 / 6,600 : GA9030
Dimensions (L x W x H)	GA7030 : 511 x 200 x 140mm (20-1/8" x 7-7/8" x 5-1/2")
	GA9030 : 511 x 249 x 140mm (20-1/8" x 9-3/4" x 5-1/2")
Net weight	5.1kg (11.2lbs)

Cordless tools
 Li-Ion
 Drilling/Fastening
 Impact
 Drilling/DEMOLITION
 Cutting
 Grinding/Sanding
 Sawing
 Planning/Routering
 Outdoor
 Power Equipment
 Dust
 Extraction/Other
 SSP Series
 Pneumatic